



KLP, INC.
 LIGHTNING PROTECTION SYSTEMS
 PROTECTING LIVES AND PROPERTY
 406-745-3800, PH 406-745-3820, FAX

www.kuefler-lightning.com
 kuefler@kuefler-lightning.com

P.O. BOX 209
 ST. IGNATIUS, MT
 59865

Aluminum – Spring Loaded Air Terminals



Common use where window washing equipment is used, etc. Spring-Mount prevents damaging or breaking of fixed Air Terminals, or in mid-roof areas where Air Terminals may be subject to breakage and/or personnel safety considerations. The stainless-steel spring allows a 90 degree tilt in any direction and has a safety tether that can be attached to an air terminal base bolt, in case of breakage. Easily retrofits to existing Lightning Protection System. Air Terminal length is determined after the spring adaptor.

| 1/2" DIAMETER | ALUMINUM - Class I | |
|------------------|--------------------|---------------------|
| | Part Number | |
| AT LENGTH (IN) | Aluminum Tapered | Aluminum Safety Tip |
| 10" | A1210SPL | A1210STSPL |
| 12" | A1212SPL | A1212STSPL |
| 16" | A1216SPL | A1216STSPL |
| 18" | A1218SPL | A1218STSPL |
| 24" | A1224SPL | A1224STSPL |

| 5/8" DIAMETER | ALUMINUM - Class I or II | |
|------------------|--------------------------|---------------------|
| | Part Number | |
| AT LENGTH (IN) | Aluminum Tapered | Aluminum Safety Tip |
| 10" | C5810SPL | C5810STSPL |
| 12" | C5812SPL | C5812STSPL |
| 16" | C5816SPL | C5816STSPL |
| 18" | C5818SPL | C5818STSPL |
| 24" | C5824SPL | C5824STSPL |