



KLP, INC.
LIGHTNING PROTECTION SYSTEMS
PROTECTING LIVES AND PROPERTY
406-745-3800, PH 406-745-3820, FAX

P.O. BOX 209
ST. IGNATIUS, MT
59865

www.kuefler-lightning.com
kuefler@kuefler-lightning.com

Lightning Conductor – Lead-Jacketed & Bare Copper



C56-19



C901LC



Lightning Conductor for Heavy-Duty smokestacks. Available in bare copper or lead-jacketed. 1/16" lead jacket for corrosion protection is required.

Typically, the top 25 feet of the stack requires lead-jacketed lightning protection equipment. Below 25 feet of the top of the stack maybe bare copper.



KLP, INC.
 LIGHTNING PROTECTION SYSTEMS
 PROTECTING LIVES AND PROPERTY
 406-745-3800, PH 406-745-3820, FAX

P.O. BOX 209
 ST. IGNATIUS, MT
 59865

www.kuefler-lightning.com
 kuefler@kuefler-lightning.com

LC = Lead Covered

Part Number	AWG	Stranding	No. of Strands	Overall Diameter	Strand Gauge	Lead Jacketed	Lbs. per 1000 ft.	Circular Mills
C56-19	2/0 Class II	Concentric	19	0.403"	12	No	410	133,100
C901LC	2/0 Class II Lead Jacketed	Concentric	19	0.545"	12	Yes	996	133,100

Note: A combined length of lead covered and bare cable may be ordered. For example, if a 200 foot length of minimum Class III conductor with the top 25 feet lead covered is required. Specify as follows:

Quantity 200' C901LC x 25' C901 x 175'