KLP, INC.
LIGHTNING PROTECTION SYSTEMS
PROTECTING LIVES ANDPROPERTY
406-745-3800, PH 406-745-3820, FAX

www.kuefler-lightning.com
kuefler@kuefler-lightning.com

P.O.BOX209
ST.IGNATIUS,MT
59865

Green Insulated Conductors

Green Insulated Conductor carries a THW or THHN rating. Intended for general purpose applications and may be installed in conduit, duct, or other recognized raceways in wet or dry conditions. (60 degrees Celsius oil/ 90 degree Celsius water; 105 degrees Celsius dry)

For both new installations/work and rewiring applications. The smaller diameter of the wire permits additional circuits or larger conductors to be installed in the conduit without exceeding the maximum fill limitations.

High quality insulation made with a heat and moisture resistant polyvinyl chloride compound over which a heat and light stabilized nylon jacker is tightly applied.

Meets Underwriters' Laboratories UL83, Federal Specification JC-30A, and Gasoline and Oil Resistant II (UL).

Sunlight Resistant, VW-1 Flame Resistant, Lead Free- ROHS Compliant, 600v.

Other Colors Available upon Request.

Part Number	Size (AWG)	No. of Strands	Jacket Type	CM Area	Approximate Weight lbs./M ft.
67G	6	7	THW2	26,240	105
67TG*	6	7	THW2	26,240	105
6-19G	6	19	THHN	26,240	98
47G	4	7	THW2	41,740	160
4-19G	4	19	THHN	41,740	157
27G	2	7	THW2	66,360	245
27TG*	2	7	THW2	66,360	245
2-19G	2	19	THHN	66,360	240
1/019G	1/0	19	THHN	105,600	372
2/019G	2/0	19	THHN	133,100	462
4/019G	4/0	19	THHN	211,600	716